


2-WAY BALL SPEAKERS

RCS



20W Adaptions 5/10/20W
2-Way-System

100 V
PASSIVE
ACTIVE



Description

These attractive ball speaker not only impress with their extraordinary design but also by a great sound. They are used in buildings with high ceilings and can then be taken down up to 5 meters.

Please consider the following features:

- These ball speakers are available in white (**W**) and black (**S**)
- Burgle proof installation and up to 5 m adjustable suspension.
- They are equipped with a high-quality 2-way coaxial chassis that in reference to sound pressure and fidelity fulfills also professional requirements.

- The fitted high-quality 100V, 20 W matching transformer prevents every loss of perfect hearing quality.
- Various connection options allow you to adjust the cable at full, half or quarter power.

with professional 2-way-coaxial-chassis



Technical data	KLC-200 W/S
Load rating (Music power)	20 (30) W
Transformer tapings at 100V	20 / 10 / 5 W
Frequency range	120 – 16.000 Hz
Sound pressure at 1W/1m	96 dB
Sound pressure SPL Pmax/1m	109 dB
Angle of refl. beam (-6dB) 1/4/8 kHz	190°
Speaker Ø (mm) and Impedance	165mm / 8 ohms 2-way-coaxial-chassis
Dimensions Ø x H (mm)	210 mm
Weight, Colour	approx. 1,8 kg; white, black

Model designations

Ball Speaker, white..... **KL-200 W**
with 100V-transformer, 20 W

Ball Speaker, black..... **KL-200 S**
with 100V-transformer, 20 W